

BASIC XL

A tower of strength

Extra strong for large openings

The Alpha Basic XL has been specially developed for large interior openings up to 36 m². All structural components and the curtain are robustly designed and engineered. Overpressure and underpressure can exert considerable forces on the door curtain. With its 1.2 mm thick door curtain and strong aluminium stiffener/hinge profiles, the Basic XL is capable of withstanding wind loads of up to 5 Beaufort (28 - 38 km/h).

Specific features:

- extra strong, fabricated steel side columns with brushes to seal and guide the door curtain
- a bottom beam with a self-testing bottom safety edge and cast aluminium end pieces of as standard
- the aluminium lower beam is available with a 'break away' crash-protection system, which prevents damage in a collision and allows the door curtain to be repositioned in the guides without having to use special tools



RETAIL

The best solution for your store!

The standard tubular motor allows elegant styling with-out taking up excessive space in the store. And if you truly want to dot your i's and cross your t's in terms of presentation, you can also print your logo or a photographic image on the PVC door curtain.

Safety is obviously the most important consideration in areas with a high customer density such as supermarkets. The Alpha Retail is equipped as standard with a Flex Edge bottom beam and an automatic emergency opening system for use in the event of a power failure.

Options

- Flex-Edge instead of aluminium lower beam
- counterweight instead of spring for balancing
- industrial integrated drive
- multiple photocells in the side guides
- mechanical emergency release
- door leaf featuring a print of your choice



The **Basic XL** is a high speed, electrically operated door, specifically designed for interior openings in industrial and commercial buildings.

Specifications	Basic XL
max. surface area (W x H)	36 m ²
max. width (W)	6000 mm
max. height (H)	6000 mm
opening speed	0.7 m/s
opening speed with frequency control	max. 1.5 m/s
closing speed	1 m/s
closing speed with frequency control	0.5 m/s
door curtain weight	1400 gr/m ²
door curtain thickness	1.2 mm

Product Benefits

- class 0 wind resistance
- safety photocell in the door opening
- completely transparent, 'Full Vision' door curtain optional

1023 2009 3020 5002 7038 9003 9004



These days, supermarkets also have to look attractive. The products on display need to be presented accessibly and appetisingly. The Alpha Retail door puts the finishing touches to a successful in-store presentation. This high speed interior door with its opening speed of 2 m/s is not just one of the fastest of its kind, it also opens and closes in near silence.

Specifications	Retail
max. width (W)	2250 mm
max. height (H)	2600 mm
opening speed	2 m/s
closing speed with frequency control	0.5 m/s
door curtain weight	650 gr/m ²
door curtain thickness	0.7 mm
door curtain thickness w. print	0.9 mm

Product Benefits

- class 1 wind resistance
- compact design of side guides and roller cover
- self-repairing after impact, in one direction
- the quietest high speed door ever!

1003 2009 3020 5005 7038 9003 9004